

# Serving the Beverage Processing Industry with Kynar® PVDF

Today's wine, beer and juice producers, home brewers, and restaurants demand materials that are easily processable, flexible, and can withstand more physical and chemical abuse. Kynar® fluoropolymers are extreme materials with specific attributes that give them the ability to replace other plastics and even stainless steel. Easily processable into pump components, tubing, fittings, pipes, and valves, Kynar® PVDF is available in various grades for demanding customer applications.

# **Key Attributes:**

- Abrasion Resistance Can outperform steel
- Low Absorption Taste of beverage is minimally affected
- Low Extractables Regulatory compliance achieved
- ••• Chemical Resistance Easy to clean and maintain
- A Complete Solution Kynar® resins can be fused together using various common methods (mechanically joined, threaded, or fusion welded)

### **KYNAR® PVDF ADVANTAGES OVER EXOTIC METALS**


Non-Corroding / No Rust	Non-Wetting / Easy Release	Chemically Inert
High Purity / Minimal Leaching	No Metallic Taste Issues	Can Clean with Aggressive Chemicals
Broad Range of Processing Equipment  Components	Lightweight	Safety - No Sharp Edges

**Industry Specifications:** Certain grades of Kynar® PVDF conform to specifications and requirements for the beverage processing industry, including FDA 177.2510 and 177.2600 for Repeated Contact with Food, Kosher Certified by Chicago Rabbinical Council (CRC), NSF 51 & 61, and USP Class VI.

**Available Grades:** A variety of grades are available with a wide range of properties. The most commonly used grades in the Beverage Industry are Kynar Superflex® 2500, Kynar Flex® 2750, Kynar Flex® 2800, Kynar Flex® 2850, Kynar® 1000 HD, and the Kynar® 700 series. Specific grade properties and characteristics can be found at <a href="mailto:ark.ma/tpamaterials">ark.ma/tpamaterials</a>.

# APPLICATIONS INCLUDE PIPING, FLEXIBLE TUBING, FITTINGS, CONNECTORS AND MORE...







Arkema's dedicated business and technical community can assist in choosing Kynar® PVDF grades. Please call 1-800-KYNAR-50 or contact us at www.kynar.com for assistance.

The Technical Polymers Food & Beverage Market page can be found at this address: ark.ma/tpa-food-and-beverage

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEWA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HERBIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe only patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations. Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids: (http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index/html)

Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices. It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final endruse product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies). It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual endruse requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.

Kynar®, Kynar Flex® and Kynar Superflex® are registered trademarks of Arkema Inc.

© 2017 Arkema Inc. All rights reserved.

### extremematerials-arkema.com

ARKEMA

**Contact Information** 

China: +86 21 61476888 Japan: +81 3 5251 9900 Korea: +82 2 370367000 Singapore: +65 64199199

Singapore: +65 64199199 Taiwan: +886 2 27476979 India: +91 22 66137500 Arkema Inc. 900 First Avenue King of Prussia, PA 19406 USA

Tel.: (+1) 610-205-7000 arkema-inc.com

## **Headquarters: Arkema France**

420, rue d'Estienne d'Orves 92705 Colombes Cedex – France Tel.: +33 (0)1 49 00 80 80 Fax: +33 (0)1 49 00 83 96 arkema.com